

## SHEET/PLATE LEAD SPECIFICATIONS

Jamestown North America offers highly customized sheet & plate lead in various thicknesses, widths and lengths. The most common sheet lead thickness ranges from 1/32" to 3/16" and can be produced in common sheet sizes, such as 30" x 30", 3' x 3', 4' x 7' and 4' x 8' as well as custom sizes based on your needs. Lead plate is also available in thicknesses 3/16" and up in standard or customized sizes.

Jamestown produces sheet & plate lead in the following grades of lead:

- Pure/Corroding grade (can meet QQL and ASTM specs),
- Chemical (Copper Bearing) grade (can meet QQL and ASTM specs) and
- Antimonial grade (can meet AMS-L-18331A spec).

Safety Data Sheets (SDS) are available for all Jamestown North America sheet lead products via our website [www.jamestownnorthamerica.com](http://www.jamestownnorthamerica.com) or upon request.

<u>THICKNESS FRACTION</u>	<u>DECIMAL EQUIVALENT</u>	<u>MM EQUIVALENT</u>	<u>LBS. PER SQ. FT.</u>
1/64"	.0156"	.3969mm	1#
1/32"	.0313"	.7950mm	2#
1/24"	.0420"	1.0670mm	2-1/2#
3/64"	.0470"	1.1930mm	3#
1/16"	.0625"	1.5875mm	4#
5/64"	.0780"	1.9812mm	5#
3/32"	.0940"	2.3786mm	6#
1/8"	.1250"	3.1750mm	8#
5/32"	.1560"	3.9675mm	10#
3/16"	.1875"	4.7625mm	12#
1/4"	.2500"	6.3500mm	16#
3/8"	.3750"	9.5250mm	24#
1/2"	.5000"	12.7000mm	30#
3/4"	.7500"	19.0500mm	45#
1"	1.000"	25.4000mm	60#
1-1/2"	1.500"	38.1000mm	90#
2"	2.000"	50.8000mm	120#